



umano medical



MENTAL HEALTH BED
FOR CLINICAL AND SAFETY NEEDS



OFFERING THE
RIGHT BALANCE
BETWEEN
CLINICAL NEEDS
AND **RISK MITIGATION**



Integrated Scale and Bed
Exit Detection System



Low Height for fall prevention
and increased safety



Concealed cables and
SafeFlex™ patient surface to
reduce apparent ligatures



Seamless Smooth Surfaces
to promote infection prevention



Ligature-resistant design
featuring tamper-resistant
parts and components



Motion control master lock out,
password protection, or motion
key lock to prevent unwanted
motions of the bed

SAFE-LOCK™
BRAKING SYSTEM
protects against unintended use of the bed



SMART SCREEN &
MOTION CONTROL MASTER LOCKOUT
brings safety to another level



POWER CORD OPTIONS Short, Quick
Disconnect, or 3-Section Rugged power
cord to reduce the risk of patient self-harm



CHOOSING THE RIGHT BALANCE BETWEEN CLINICAL NEEDS AND RISK MITIGATION



LOW OBSERVATION ENVIRONMENTS

Med-Surg Psych / Geriatric / Emergency Departments
Option 1

MENTAL HEALTH FEATURES

- Tamper-resistant design (fasteners, accessory socket caps)
- Permanently attached boards*
- Filled boards & siderails
- Safe-Lock™ braking system
- SafeFlex™ patient surface
- Concealed cables
- Battery powered patient positioning
- Covered restraint points
- Calm gray aesthetic design

BED FEATURES

- 25.4 cm / 10" low height (12.7 cm / 5" dual casters)
- Motion control lockout on footboard
- Integrated bed exit detection system (3-levels of sensitivity)
- Bed exit side view lights
- Siderail controls with one-touch clinical bed positions
- Nurse call connector
- CPR release handle

SMART SCREEN / PATIENT MONITORING

- Motion control master lock out / password protection
- Minimum height management
- Alarms and reminders
- Inform Safety Message Center
- History and logs

POWER CORD OPTIONS

- Short power cord (3 ft) / 0.9 m
- Quick-disconnect power cord (8 ft) / 2.4 m
- 3-Section Rugged power cord (3 ft) / 0.9 m

OPTIONAL FEATURES

- Motion key lock
- Integrated scale
- Heavy-duty metal caster cover
- Tamper-resistant hardware tools
- Communication port
- Auxiliary power outlets at foot end
- Dual nightlights with Smart Nightlights™ technology¹
- Additional siderail controls:
Backlight, reading/room lights, nurse call

* Not intended to be used in critical or acute care environments.

¹ Available with quick-disconnect power cord only

Umano Medical reserves the right to change specifications without notice.

HIGH OBSERVATION ENVIRONMENTS

Dedicated Psychiatric Units / Detention Centers
Option 2

MENTAL HEALTH FEATURES

- Tamper-resistant design (fasteners, accessory socket caps)
- Permanently attached boards*
- Filled boards
- No siderails
- Safe-Lock™ braking system
- SafeFlex™ patient surface
- Concealed cables
- Heavy-duty metal caster cover
- Calm gray aesthetic design

BED FEATURES

- 25.4 cm / 10" low height (12.7 cm / 5" dual casters)
- Motion control lockout on footboard

POWER CORD OPTIONS

- Short power cord (3 ft) / 0.9 m
- Quick-disconnect power cord (8 ft) / 2.4 m
- 3-Section Rugged power cord (3 ft) / 0.9 m

OPTIONAL FEATURES

- Motion key lock
- Floor mount
- Filled siderails
- Covered restraint points or heavy-duty restraint loops
- Tamper-resistant hardware tools
- CPR release handle

EACH CARE ENVIRONMENT IS DIFFERENT. EACH PATIENT IS UNIQUE.

Reach out to your sales representative for a customized configuration of the ooksnow^{MH} to meet your clinical needs and risk mitigation plan.

FL36 / FL36-SC TECHNICAL SPECIFICATIONS

Patient Surface Dimensions	88.9 cm x 203.2 cm or 213.5 cm 35" x 80" or 84"
Overall Width	Siderails down 100 cm / 39.25"
	Siderails up 102.9 cm / 40.5"
Safe Working Load	600 lb / 272 kg
Height Range (to litter top)	Low 25.4 cm / 10"
	High 76.2 cm / 30"
Patient surface positioning	
Backrest	0° to 60°
Knee Gatch	0° to 30°
Trend. / Reverse Trend.	± 16°
Certifications / Standards	IEC 60601-2-52 IEC 60601-1 3rd Edition 120-240 V AC
Volts	120-240 V AC
Ampere Rating	4.25 A (9.25 A with 120 V outlets)
Current Leakage	< 300 micro amps
Frequency	50-60 Hz
Power Plug	Hospital grade
Battery type	Sealed rechargeable lead acid
	1.2 Ah, 2 * 12 V
Scale System Accuracy (EC)	OIML Class III ±0.5 kg

For complete specifications, please refer to the user manual.